


1 1/2" BORE STAINLESS STEEL CYLINDER



EBR-24-□-□

Double Acting, Rear Spring Bias

Mount: End
Type: Rotating Rod
Options: M, B, H, W, V, P6, P7, P8, N
Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4"
Spring Compressed: 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Maximum Stroke: 14"




Nuts included, but not shown on drawing

EFR-24-□-□

Double Acting, Front Spring Bias

Mount: End
Type: Rotating Rod
Options: M, B, H, W, V, P6, P7, P8, N
Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4"
Spring Compressed: 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Maximum Stroke: 23"




Nuts included, but not shown on drawing

SFD-24-□-□

Double Acting, Front Spring Bias

Mount: Stud
Type: Double Rod
Options: M, B, H, W, V, P6, P7, P8, N
Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4"
Spring Compressed: 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Maximum Stroke: 14"




Nuts included, but not shown on drawing

SBR-24-□-□

Double Acting, Rear Spring Bias

Mount: Stud
Type: Rotating Rod
Options: M, B, H, W, V, P6, P7, P8, S, N
Standard Stroke Lengths: 1/2", 1", 1-1/2", 2", 3", 4"
Spring Compressed: 10 lbs. **Spring At Rest:** 4 1/2 lbs.
Maximum Stroke: 15" For S option add 0.187



Nuts included, but not shown on drawing