



Maximatic Filters, Regulators & Lubricators

Maximatic FRLs condition and prepare compressed air for use in fluid power systems. Pneumatic applications with properly conditioned air will operate longer, cost less and improve system efficiency. Clippard offers five different sizes from #10-32 to 1" NPT of Filter, Regulators, Lubricators and combination units. Their modular design and interconnecting brackets provide flexibility and facilitates simple field installation and/or modification.

Filters. Filters capture solid particulate and remove water by "spinning" the air centrifugally. Water and larger particles are thrown against the side of the bowl where they condense and/or fall to the lower part of the bowl. Smaller particles are captured as the air flows through the filter element.

Regulators. Controlling pressure is an important requirement in all systems. Maximatic Regulators are adjustable from 7 to 125 psig. For applications requiring better resolution, 7 to 30 or 7 to 60 psig models with spring are available. The #10-32 size is a piston-style due to its small size, while the 1/8" to 1" are a diaphragm design.

Lubricators. Pneumatic actuators and valves perform better and last longer when properly lubricated. The bowl serves as a reservoir for the oil and supplies oil through the pick-up tube when pressurized. The amount of oil dispersed is controlled by an adjustable needle valve.

- Body Material:** Die Cast Aluminum
- Maximum Operating Pressure:** 150 psig
- Regulating Range:** 125 psig standard, 30 psig and 60 psig optional
- Regulator Type:** Relieving
- Filter Drain:** Semi-Automatic Differential or Optional Automatic Drain. When the air supply is below 7 psig, the semi-automatic drain will open.
- Bowl Material:** Polycarbonate standard up to 4Z model/size. Metal bowl standard on 4A and 5B models/sizes. Aluminum Cast with sight glass available.
- Bowl Guard:** Steel on models indicated
- Filtration:** 25 micron sintered brass filter standard, 5 micron optional
- Temperature Range:** 32 to 130°F (-0 to 54°C)

Ordering Guide

Type	Enter	Enter							
FRL	.FRL	Filter	.F	<input type="text"/>					
Stacking FRL	.FRLS	Regulator	.R		<input type="text"/>				
Stacking Filter-Regulator	.FRS	Lubricator	.L						
Body/Port Size	Enter	Enter							
#10-32	.1N	3/8" NPT (High Flow)	.4W						
1/8" NPT	.2P	1/2" NPT	.4Z						
1/4" NPT (Standard Flow)	.2Q	3/4" NPT	.4A						
1/4" NPT (High Flow)	.3Q	1" NPT	.5B						
3/8" NPT (Standard Flow)	.3W								
Options									
		Automatic Drain (D)			Metal Bowl (M)		30 psig (P30)	5 Micron Filter (F5)	
		<input type="text"/>			<input type="text"/>		<input type="text"/>	<input type="text"/>	

This numbering schematic is shown for illustration purposes only. All possible configurations are not available—For standard models, see the products illustrated in this catalog.

Example: MM - -